

Peristaltic pumps

The peristaltic pump CEP and a new transport system do soft and delicate ideal for the transport of fluids, more or less dense.

The pump is suitable for working fluids such as "wine - fruit juice - milk - oil" or semisolid products such as "whole grapes - crushed - stemmed - tomato - fruit salad - grapes", or abrasives as Marc, thanks to the insulation system product content is never in contact with the pumping member and therefore is not subject to oxidation contamination, shaking, emulsions, also berries, seeds and stems are not crushed it polluted by harmful particles .

Optional:loading hopper with auger



TECHNICAL DATA

Model	Hourly Prod	Motor	Outlet connection	Dimension hopper	Total size
PINOX 60 2	25-	1,5	Ga. Ø 40	750x750xh430mm	860x420xh920mm
speed	50HL/h	1,5	Ga. Ø 40	750x750xh430mm	860x420xh920mm
PINOX 60	2 a	2,2	Ga. Ø 40	750x750xh430mm	1150x600xh1100mm
w/INVERTER	50HL/h	3	Ga. Ø 60	750x750xh430mm	1150x600xh1100mm
PINOX 80	5 a	4	Ga. Ø 80	750x750xh430mm	1300x700xh1300mm
w/INVERTER	80HL/h	4	Ga. Ø 80	750x750xh430mm	1300x700xh1300mm
PINOX 150 2	65-	7,5	Ga. Ø 100	750x750xh430mm	1400x780xh1600mm
speed	130HL/h	11	Ga. Ø 100	750x750xh430mm	1600x850xh1350mm
PINOX 150	17 a				
w/INVERTER	130HL/h	15	Ga. Ø 120	750x750xh430mm	1700x950xh1650mm
PINOX 300	48 a				
w/INVERTER	280HL/h				
PINOX 320 2	160-				
speed	320HL/h				
PINOX 450	94 a				
DOUBLE	450HL/h				
w/INVERTER					
PINOX 650	123 a				
DOUBLE	640HL/h				
w/INVERTER					

